



PROCROSS F800 TUCKER HIBBERT RACE REPLICA

ENGINE TYPE, DISPLACEMENT (cc)	2-stroke, 794	SKI TYPE/WIDTH	White trail ski/6"	BRAKES	Race radial master cylinder hydraulic brake / race disc on drive shaft
ENGINE COOLING, CYLINDERS	liquid, twin	SKI RUNNER TYPE	single runner w/carbide	FUEL CAPACITY (gal.)	10.6
BORE X STROKE (mm)	85 x 70	FRONT SUSPENSION	Arctic Race Suspension with FOX EVOL X Kashima Coated shocks with compression and rebound adjustability and sway bar	LENGTH x WIDTH (in.)	118 x 48
LUBRICATION	oil injection	FRONT SKI TRAVEL (in.)	10	STANDARD FEATURES	push button engine reverse, dual halogen headlight (2-bulb), front bumper, adjustable handlebar, low-height windshield, deluxe digital/analog gauge, electric gas gauge, low oil light, coolant overheat light, accessory outlet, high/low hand warmer, high/low thumb warmer, tether switch, belt holder, air pump, handguards, number plates, non-slip seat cover
IGNITION	3D	REAR SUSPENSION	ProCross Race Slide-action suspension with 7-position coupling, FOX ZERO X Piggyback front and rear shocks with adjustable dampening	OPTIONAL FEATURES	electric start, front sport bumper, hitch, rack, 2-up seat, storage bags, tank pads, (ex low, flyscreen, low, mid, high) windshield, mirrors
CARBURETION	46 mm dual throttle body batteryless EFI	REAR WHEEL TRAVEL (in.)	13.5	AVAILABLE COLORS	Black/Black
REQUIRED FUEL	91 octane	TRACK WIDTH X LENGTH X LUG (in.); TYPE/PITCH	15 x 128 x 1.25 RipSaw II / 2.86" pitch		
EXHAUST SYSTEM	APV with tuned pipe, pipe sensor and stainless steel muffler	CHASSIS	ProCross		
DRIVE CLUTCH	Arctic 6 post (rpm sensing)				
DRIVEN CLUTCH	10.75" dia Arctic (roller cam)				
DRIVE SYSTEM	Arctic Drive System				
SKI STANCE (in.)	42-43 adjustable				

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

2013 ARCTIC CAT TECHNICAL SPECIFICATIONS

